



<p>Product highlights</p>	<p>Polyester railway enclosure (PG 62)</p> <ul style="list-style-type: none"> • Robust plastic enclosure for railway industry • Universal construction for multifunctional use • Certificated acc. to EN 45545 	<p>E30 Fire protection enclosures (PG E30)</p> <ul style="list-style-type: none"> • Fire protection enclosure from special halogen free polyester material • Enclosure system with general certification to DIN 4102 part 12 • Individual modification with special approval ceramic terminal blocks and cable glands
<p>Technical data</p>		
<p>Material</p>	<p>glass fibre reinforced thermoset polyester</p>	<p>glass fibre reinforced thermoset polyester</p>
<p>Ingress protection</p>	<p>IP66 to EN 60529</p>	<p>IP66 to EN 60529</p>
<p>Impact resistance</p>	<p>IK07 to IEC 60068-2-75</p>	
<p>Seal</p>	<p>>10¹² Ohm, IEC 600</p>	<p>CR round seal</p>
<p>Toxicity</p>	<p>halogen free</p>	<p>halogen free</p>
<p>Colour</p>	<p>RAL 7047, telegrey 4</p>	<p>RAL 2004, orange</p>
<p>Temperature range</p>	<p>-40°C to +130°C with silicone seal</p>	<p>-40°C to +90°C with CR round seal</p>
<p>Approvals</p>	<p>HL 2 / HL 3 acc. to EN 45545-2</p>	<p>E30 acc. to DIN 4102-12</p>
<p>Dimensions (H x W x D)</p>	<p>75 x 80 x 56 mm to 250 x 400 x 161 mm</p>	<p>120 x 120 x 90 mm to 250 x 260 x 120 mm</p>
<p>Accessories</p>	<p>Mounting plate DIN rail, earth rail External mounting brackets External hinge</p>	<p>Cable glands Clamps</p>
<p>Included in delivery</p>	<p>Plastic enclosure in glass fibre reinforced polyester consisting of lid, seal, incl. captive +/-stainless steel screws, base with 2 or 4 earthing screws</p>	<p>Enclosure system with DIN rail and external brackets. Optimal with machining and for the enclosure system with approved terminals and cable glands.</p>