

## Commander 450



- + Control enclosure in stainless steel 1.4301 (304)
- + Different handle design versions
- + High protection class IP66
- + Integrated grounding lugs
- + Customized laser processing possible
- + Optional further locking systems made of different materials available (e.g. plastic or zinc die-cast)

### Included in delivery

Enclosure including reinforcing plate, couplings hole and handles.

### Technical data

Material	Stainless steel 1.4301/304 other materials on request
Surface	grinded, grain 320
Seal	Silicone
Ingress protection	IP66
Temperature range	-20 °C to +80 °C



# Commander 450

## Product range

Order No.	Dimensions (mm) W x H x D	Fitting (mm) W x H	Variation	Drillings for suspension system (Side A)	Weight (kg)
56.45 01 01	400 x 300 x 120	300 x 200	with two edge handles (side C/D)		4.21
56.45 01 02	400 x 300 x 120	300 x 200	with two bow handles (side C/D)		5.68
56.45 01 03	400 x 300 x 120	300 x 200	with one bow handle (side B)		5.40
56.45 02 01	400 x 300 x 160	300 x 200	with two edge handles (side C/D)		4.90
56.45 02 02	400 x 300 x 160	300 x 200	with two bow handles (side C/D)		6.37
56.45 02 03	400 x 300 x 160	300 x 200	with one bow handle (side B)		6.09
56.45 03 01	400 x 400 x 160	300 x 300	with two edge handles (side C/D)		7.13
56.45 03 02	400 x 400 x 160	300 x 300	with two bow handles (side C/D)		7.84
56.45 03 03	400 x 400 x 160	300 x 300	with one bow handle (side B)		7.24
56.45 04 01	500 x 300 x 200	400 x 200	with two edge handles (side C/D)		7.49
56.45 04 02	500 x 300 x 200	400 x 200	with two bow handles (side C/D)		8.38
56.45 04 03	500 x 300 x 200	400 x 200	with one bow handle (side B)		8.26
56.45 05 01	500 x 500 x 200	400 x 400	with two edge handles (side C/D)		9.00
56.45 05 02	500 x 500 x 200	400 x 400	with two bow handles (side C/D)		12.00
56.45 05 03	500 x 500 x 200	400 x 400	with one bow handle (side B)		11.00

